

Smart Home Controller 2.2 Release Notes

Contents

Eaton-SHC-7.5-2.2.x	3
System Update Notes and Recommendations	3
Features and Enhancements	3
New xComfort Room Controller Touch support.....	3
Climate Function Update	3
Planner Update	3
Enhancements	3
Fixed Issues.....	4
Automatic switching of climate to protection mode and back based on window sensors is not reliable.....	4
Camera configuration not correctly saved, missing camera in zone after update.....	4
Light devices are listed twice in the list, double light icons in dashboard.....	4
Devices deleted from zone can be still available for function configuration	4
Switching actuator configured for heating available in status and control function	4
Encoded passwords in SHC configuration	4
Changes to device configuration can't be saved or saving takes a lot of time.....	4
The system turn on the heating even if the measured temperature is above the set temperature	4
An offset to climate function event is applied when inertia is switched off	5
Trigger events in macro for various device functions.....	5
Alarm function with smoke sensor	5
Offset in the System/Devices for energy sensors doesn't influence the energy function....	5
Planner event created in Web View as Sunrise / Sunset is presented as 12:00 time event instead.....	5
Missing multi heating actuator icons in Macro function.....	5
Deleted planner events are present and active after reboot of SHC	5
Binary Input events description in recording files, content of recordings is not correct.....	5
Web client can't show alarm and system events	5
xComfort devices can't communicate with SHC after import of configuration.....	5
Status of switching/dimming actuator in Web View is not updated	6

If user changes the climate setpoints from the Admin Console, the actual setpoint on the Web View dashboard remains unchanged 6

Outside Temperature not shown in Dashboard 6

SHC doesn't support the Group of Analog Actuators 6

Icon for locked actuator is missing in Web View 6

The number of switched-on lights is not correctly shown 6

Status and control function doesn't show correctly binary input of markers 6

System can't start after power off / power on 6

Missing macros after restart 6

Known Issues..... 6

 Macro doesn't work after changing the device type 6

 Planner event name "null" 7

 Users are deleted after import MRF file 7

 Status & Control Function order of devices 7

 Alarm Function Armed/Disarmed in Main Dashboard..... 7

Workarounds in case of update from 1.1.30 -> 2.x.x..... 7

 ECIs should be on-line 7

 Group devices not displayed correctly 7

 Old devices can appear again 7

 Missing group devices in Macros or Scenes 7

Eaton-SHC-7.5-2.2.x

System Update Notes and Recommendations

- Floor heating protection function needs re-configuration: Go to the 2.System/Devices and select “Floor Temperature” function for your temperature sensors and “Floor Heating” function for actuators that are used for floor heating control. These device functions were not available in older versions of SHC system. Then re-configure floor heating protection in the 3.Advanced/Functions/Climate Function of all respective zones.
- Go to the 1. Diagnostics/System Status and check whether OS and BL update button is available in OS version row. Perform the update if the button is available.
- Always take backup of your SHC configuration and History Data before any changes to your configuration.
- Do not power-off your SHC immediately after configuration changes to restart the system. It takes some time to process changes and to store your configuration on the background.

Features and Enhancements

New xComfort Room Controller Touch support

- Room Controller Touch supported in Climate Function.
- Climate Function mode and parameters configurable from Room Controller Touch.
- RF module firmware (2.20) has to be updated to support new Room Controller Touch.

Climate Function Update

- If the protection time is defined for Climate Function in the Web Admin Console a window pop ups to inform on the required configuration of cyclic sending time in MRF.
- Climate function stops heating based on zone temperature and setpoint regardless of Radiator Valve position.
- When learning mode is selected the inertia value is set to “Slow” by default and it is not possible to switch off the inertia.
- Temperature sensor timeout is available as macro trigger.
- Floor heating protection temperature range extended to a range 20–60°C.
- Floor heating actuators available to limit protection function only to floor heating.
- Climate type can be controlled by macro.
- Main heating device is controlled only by climate zone where the device is enabled.

Planner Update

- When you start editing a planner event the whole group of events is highlighted so you can see what will be changed.
- You can easily recognize single and group planner events.
- Improved handling of planner with large number of events including saving process.

Enhancements

- It is possible to use diacritics for APN and GCM messages.
- It is possible to use diacritics for user name and password.
- Changes in handling of internal logging files to improve stability of the system.
- Improved handling of internal SHC configuration to avoid stability issue.

- Improved internal processing of sensor values so there is consistent information on sensor value in all user interfaces.
- Improved user passwords encoding during SHC cfg backup / restore.
- Changes of device configuration trigger function re-initialization so functions reflect actual device configuration.
- Several localization problems were fixed .

Fixed Issues

Automatic switching of climate to protection mode and back based on window sensors is not reliable

Issue with proper handling of more than one window sensor was fixed.

Camera configuration not correctly saved, missing camera in zone after update

Existing cameras keeps the same ID after import or configuration so the system can use them in a proper way.

Light devices are listed twice in the list, double light icons in dashboard

For a specific configuration of switching actuators it could be that multiple light icons were presented in dashboard or switching actuators could be listed more times during macro configuration. Such incorrect behavior was fixed.

Devices deleted from zone can be still available for function configuration

Devices deleted from zone could be still available in previously configured functions. Such incorrect behavior was fixed and devices are now available for functions only if they are assigned to the respective zone.

Switching actuator configured for heating available in status and control function

If function of a switching actuator device was changed in Web Admin/System/Devices to heating the device was still available in status and control function if it was enabled for the status and control function previously. Heating devices are not now available in status and control after such re-configuration.

Encoded passwords in SHC configuration

A possibility to get double encoded password in the SHC configuration during export was eliminated.

Changes to device configuration can't be saved or saving takes a lot of time

The way of internal saving of SHC configuration was improved so saving is now done for specific part of configuration only.

The system turn on the heating even if the measured temperature is above the set temperature

Climate function was updated to eliminate problems that could be caused by floor protection function.

An offset to climate function event is applied when inertia is switched off

Climate function was updated to eliminate problems that could be caused by floor protection function.

Trigger events in macro for various device functions

Adjusted the available trigger events for the various device functions.

Alarm function with smoke sensor

The binary input defined for smoke function is now working correctly in the alarm function.

Offset in the System/Devices for energy sensors doesn't influence the energy function

Both Offset and Basic Value had to be set to a numeric value to have offset functions working. If the value is not configured it is handled as zero now.

Planner event created in Web View as Sunrise / Sunset is presented as 12:00 time event instead

If User created a planner event for Sunrise / Sunset and then tried to create next Sunrise / Sunset event, the event was created and presented as 12:00 time event.

Missing multi heating actuator icons in Macro function

References to icons were fixed.

Deleted planner events are present and active after reboot of SHC

If no other configuration action was done for planner events than deleting, the result of such action was not stored to SHC configuration and after reboot deleted planner events were present again in the system.

Binary Input events description in recording files, content of recordings is not correct

The description of events in recording files was reviewed and fixed so the content contains understandable information for the user.

Web client can't show alarm and system events

The SHC saves the history of all Alarm Events and System Events. The problem was that the information couldn't be retrieved and shown in case there is too much history data. SHC and Web Client was updated so user can scroll through history data.

xComfort devices can't communicate with SHC after import of configuration

The synchronization of SHC system startup was improved so communication protocol handlers are started in the required order to eliminate possible problems with RF communication after import or reboot of SHC.

Status of switching/dimming actuator in Web View is not updated

System was updated so the status of switching/dimming actuators in Web View reflects current status of the actuator.

If user changes the climate setpoints from the Admin Console, the actual setpoint on the Web View dashboard remains unchanged

Web View data are now synchronized with Web Admin so the same setpoints are shown in the Function tab of Web Admin, Web View and dashboard of the Climate Function.

Outside Temperature not shown in Dashboard

Functions are re-initialized on device configuration changes properly so they reflect correctly actual configuration.

SHC doesn't support the Group of Analog Actuators

Analog Actuator groups are visible under devices and now it is possible to use them in configuration of zones.

Icon for locked actuator is missing in Web View

Missing icon is now available.

The number of switched-on lights is not correctly shown

Group devices were included in the total number of switched-on lights. It was corrected so only real devices are counted.

Status and control function doesn't show correctly binary input of markers

Custom On / Off for binary input of markers is now used correctly.

System can't start after power off / power on

In specific situation the system can't start after re-power any more. This can be eliminated by update of boot loader which is available in Web Admin, Diagnostics section. The update button is available only in the case the update is applicable to the specific SHC, it is recommended to perform the update if it is available.

Missing macros after restart

The way how configuration is stored was improved.

Known Issues

Macro doesn't work after changing the device type

In case a device type is changed which is already used in a macro, it is possible that the state values does not match the new type anymore. In this case the macros doesn't work anymore. Always edit the changed devices in macros.

Planner event name “null”

A Planner event pointing to a deleted macro will show “null” instead of the deleted macro name. Workaround: Remove the Planner event.

Users are deleted after import MRF file

SHC configuration file can be created both by MRF and SHC Web Admin Console. Be sure that all changes done by SHC Web Admin Console are present in back-up and the back-up is imported into MRF project before you export SHC configuration from MRF and use the configuration in SHC.

E.g. if users are created in the SHC but not yet imported in MRF the Users will be deleted after import of the MRF file which not contain this information.

Status & Control Function order of devices

The order and display preferences of devices in the Status & Control Function is only supported in the Web View. Workaround: If the order of Devices needs to be changed, login via a browser as Advanced User and click the edit button in the Status & Control Function.

Alarm Function Armed/Disarmed in Main Dashboard

The Alarm Function Armed/Disarmed Tile in the Main Dashboard is only supported in the Web View. Workaround: Enable/Disable the Alarm in Scenes (like Sleep, Away, Armed or Disarmed). Enable the Scene buttons to show on the Main Dashboard.

Workarounds in case of update from 1.1.30 -> 2.x.x

ECIs should be on-line

In case of a 1.1.30 update all ECIs in the system should be on-line during the update. Always make a backup of your system before starting the update. In case of missing devices after the update, use the MRF tool to convert your configuration files (SHC cfg, MRF project) to the new format and import the converted configuration to your SHC.

Group devices not displayed correctly

Importing 1.1.30 SHC configuration to SHC 2.0 may result in problem with group devices not displayed correctly: Import the 1.1.30 SHC configuration in MRF, do the export of configuration in MRF and then import the "new" configuration into SHC.

Old devices can appear again

Recently removed devices can appear again after update: Use MRF to remove these group devices and then import the new configuration in the SHC.

Missing group devices in Macros or Scenes

In case of missing group devices in Macros or Scenes after the update: Check the Macros/Scenes for missing group devices and replace the missing group with the existing one. The name of the group devices can be found in the System/Devices tab.