



20-50

Oppvarming & Kjøling

INNEDEL			FTXS20K	FTXS25K	FTXS35K	FTXS42K	FTXS50K	FTXS60G	FTXS71G
Kjøle kapasitet	Min./Nom./Maks.	kW	1.3/2.0/2.8	1.3/2.5/3.2	1.4/3.5/4.0	1.7/4.2/5.0	1.7/5.0/5.3	1.7/6.0/6.7	2.3/7.1/8.5
Varme kapasitet	Min./Nom./Maks.	kW	1.3/2.5/4.3	1.3/2.5/4.7	1.4/4.0/5.2	1.7/4.4/6.0	2.3/5.8/6.5	1.7/7.0/8.0	2.3/8.2/10.2
EER/COP			4.65/4.75	4.39/4.67	4.07/3.79	3.55/4.0	3.02/3.22	3.42/3.79	3.02/3.22
Maksimal varmekapasitet ved -15°		kW	-	-	-	-	-	-	-
Årskjølefaktor SEER			7.40	7.90	7.47	6.80	6.80	5.35	5.23
Årvarmefaktor SCOP			4.77	4.78	4.85	4.20	4.20	3.75	3.59
Dimensjoner	(høyde x bredde x dybde)	mm	289x780x215			295x900x215		290x1050x250	
Vekt		kg	8			10			
Luftmengde	Kjøling	H/M/L/S	m ³ /min	8.8/6.7/4.7/3.9	9.1/7.0/5.0/3.9	11.2/11.2/5.8/4.1	11.2/11.2/7.0/4.1	11.9/11.9/7.4/4.5	16.0/13.5/11.3/10.1
	Oppvarming	H/Nom.	m ³ /min	9.5/7.8	10.0/8.0	12.1/9.3	12.4/10.0	13.3/10.8	17.2/14.9
Lydeffekt	Kjøling	H	dBA	58	58	59	59	60	61
	Oppvarming	H	dBA	56	57	60	60	62	60
Lydtrykk	Kjøling	H/M/L/S	dBA	40/32/24/19	41/33/25/19	45/37/29/19	45/39/33/21	46/40/34/23	45/41/36/33
	Oppvarming	H/M/L/S	dBA	40/34/27/19	41/34/27/19	45/39/29/19	45/39/33/22	47/40/34/24	44/40/35/32
Kuldemedium		type	R-410A						
Rørkoblinger	Væske/gass/avløp	"/mm	1/4 / 3/8 / 1/8						1/4 / 1/2 / 1/80
Strømforsyning		Hz/V	230V/1ph/50Hz						1/4 / 5/8 / 1/80

UTDEL			RXS20L	RXS25L	RXS35L	RXS42L	RXS50L	RXS60L	RXS71F8	
Dimensjoner	(høyde x bredde x dybde)		mm	550x765x285	550x765x285	550x765x285	550x765x285	735x825x300	735/825/300	770/900/320
Vekt			kg	34	34	34	39	47	48	71
Energiklasse				A++	A++	A++	A++	A++		
Luftmengde	Kjøling			A++	A++	A++	A++	A++		
	Oppvarming			A++	A++	A++	A++	A++		
Lydeffekt	Kjøling	H/L	m³/min	33.5/30.1	33.5/30.1	36/30.1	37.3/30.6	50.9/48.9	50.9/42.4	54.5/57.1
	Oppvarming	H/L	m³/min	28.3/25.6	28.3/25.6	28.3/25.6	31.3/27.2	45/43.1	46.3/42.4	52.5/46.0
Lydtrykk	Kjøling	Nom./H	dBA	-59	-59	61	61	62	63/-	66/-
	Kjøling	H/L/S	dBA	46/43	46/43	48/44	48/44	48/44/-	49/46/-	52/49/-
Driftsområde	Oppvarming	H/L/S	dBA	47/44	47/44	48/45	48/45	48/45/-	49/46/-	52/49/-
	Kjøling	Min.-max.	°CDB			-10-46				
Kuldemedium	Oppvarming	Min.-max.	°CWB	-15-18	-15-18	-15-18	-15-18	-15-18	-15-20	-15-20
			type			R410A				
Rørlengde						20/15				
Strømforsyning	Maks lengde/høydeforskjell		Hz/V			230V/1ph/50Hz			30/20	